



## Basic Horizontal PDU

**Part #** 8BH20-BA12Z-K1A.....  
**Description** PDU,BASIC,HORZ,2PE,IEC,12XC13,230V/16A

### SPECIFICATIONS

Physical Properties	
Dimensions	483 x 116 x 44.4mm (19.016 x 4.567 x 1.748")
Orientation	Horizontal
Footprint	19" Rack Mount
Mounting Method	Both Ends Bracket Mounting
Case Material	Aluminum
Case Color	Black
Shipping Weight	3kg

Electrical Properties	
Voltage	230VAC
Current	16A
Frequency	50/60 Hz
Input Plug	2PE
Plug Cable Color	Black
Input Cable Wire Gauge	3x14AWG
Input Cable Length	3.0m (10ft) (±76.20mm)(±3.0in.)
Power Entry Cable Length	Rear Entry
Output Socket #1	12/Black x C13
Output Socket #1 Voltage	230VAC
Load Capacity	3680VA (3.68kW)
Circuit Protection	None

Environmental	
Temperature Operating Range	10-45°C / 50-113°F
Relative Humidity Min	5%
Relative Humidity Max	95%
Elevation	0-3000m

Safety	
Certification/Agency Approvals	IEC/EN 60950-1
Certification/Agency Approvals	EN 55022 Class A
Certification/Agency Approvals	EN 55024
Certification/Agency Approvals	EN 61000-3-2
Certification/Agency Approvals	EN 61000-3-3
Certification/Agency Approvals	RoHS
Certification/Agency Approvals	REACH

**Worldwide Headquarters**  
 North America  
 Watertown, CT USA  
 Phone (1) 860 945 4200 US  
 Phone (1) 888 425 6165

**Regional Headquarters**  
 Europe/Russia/Africa  
 Chertsey, Surrey, England  
 Phone (44) 0 1932 571771

**Regional Headquarters**  
 China  
 Shanghai, P.R. China  
 Phone (86) 21 5385 0303

**Regional Headquarters**  
 Latin America  
 Bogota, Columbia  
 Phone (571) 657 1950

**Regional Headquarters**  
 India / Middle East  
 Dubai, United Arab Emirates  
 Phone (971) 43689743

**Regional Headquarters**  
 Asia Pacific  
 Sydney, Australia  
 Phone (61) 28977 7500