



Metered Horizontal PDU

Part #	Description
8TH22-BA12Z-K1A.....	PDU,METER,HORZ,2PE,IEC,12XC13,230V/32A

SPECIFICATIONS

Physical Properties	
Dimensions	483 x 116 x 44.4mm (19.016 x 4.567 x 1.748")
Orientation	Horizontal
Footprint	19" Rack Mount
Mounting Method	Both Ends Bracket Mounting
Case Material	Aluminum
Case Color	Black
Shipping Weight	2.5kg

Electrical Properties	
Voltage	230VAC
Current	32A
Frequency	50/60 Hz
Input Plug	2PE
Plug Cable Color	Black
Input Cable Wire Gauge	3x10AWG
Input Cable Length	3.0m (10ft) (±76.20mm)(±3.0in.)
Power Entry Cable Length	Rear Entry
Output Socket #1	12/Black x C13
Output Socket #1 Voltage	230VAC
Load Capacity	7360VA (7.36kW)
Circuit Protection	32A 1-Pole Breaker

Environmental	
Temperature Operating Range	10-45°C / 50-113°F
Relative Humidity Min	5%
Relative Humidity Max	95%
Elevation	0-3000m

Safety	
Certification/Agency Approvals	IEC/EN 60950-1
Certification/Agency Approvals	EN 55022 Class A
Certification/Agency Approvals	EN 55024
Certification/Agency Approvals	EN 61000-3-2
Certification/Agency Approvals	EN 61000-3-3
Certification/Agency Approvals	RoHS
Certification/Agency Approvals	REACH

Metering Accuracy	
Meter Accuracy	+/-1% (Unless Otherwise Specified)

General Functions	
Built in Display	LCD Display
Hard Reboot Button	Yes
Measurement Level	V, A

Worldwide Headquarters
 North America
 Watertown, CT USA
 Phone (1) 860 945 4200 US
 Phone (1) 888 425 6165

Regional Headquarters
 Europe/Russia/Africa
 Chertsey, Surrey, England
 Phone (44) 0 1932 571771

Regional Headquarters
 China
 Shanghai, P.R. China
 Phone (86) 21 5385 0303

Regional Headquarters
 Latin America
 Bogota, Columbia
 Phone (571) 657 1950

Regional Headquarters
 India / Middle East
 Dubai, United Arab Emirates
 Phone (971) 43689743

Regional Headquarters
 Asia Pacific
 Sydney, Australia
 Phone (61) 28977 7500