


CATEGORY 6A F/FTP CABLE - LSOH (INTERNATIONAL)

Siemon's category 6A / Class E_A 4-pair F/FTP cable supports channel performance exceeding ANSI/TIA and ISO/IEC category 6A requirements. This cable uses a 5-foil screened design consisting of 4 individual foils wrapped pairs plus an overall foil shield. When combined with our shielded Z-MAX® 6A connectivity, the end result is a channel capable of supporting 10GBASE-T operation over 100-meter, 4-connector topologies. In addition, the fully shielded construction ensures virtually zero alien crosstalk.

Z-MAX 6A NETWORK CABLING SOLUTIONS




COMPLIANCE

- ISO/IEC 11801 Ed 2.2 (Class E_A)
- ANSI/TIA-568-C.2 (Category 6A)
- IEC 61156-5 Ed 2.0 (Category 6A)
- IEC 60332-1, IEC 60754-2, IEC 61034
- EN 50399 Class D s₂d_{2a1}

CABLE CONSTRUCTION

- Conductor Insulation: Foam PE
- Material: LSOH
- Drain Wire: (Solid Tinned Copper)
- Aluminium Foil Overall Shield
- Conductor: 23 AWG (0.56mm) Solid Copper
- Aluminium Foil Pair Shield



ELECTRICAL SPECIFICATIONS

DC Resistance	<7.32 Ω/100m
DC Resistance Unbalance	5%
Mutual Capacitance	5.6 nF/100m
Capacitance Unbalance	<160pF/100m
NVP	74%
TCL	40-10 log (f)dB
Coupling Attenuation	≥55 dB
Delay Skew	<20ns/100m max.

PHYSICAL PROPERTIES

	LSOH
Pulling Tension (max)	110N (25 lbf)
Bend Radius (min)	50mm (2.0 in.)
Installation Temperature	0 to 50°C (32 to 122°F)
Operating Temperature	-20 to 75°C (-4 to 167°F)

TRANSMISSION PERFORMANCE



GUARANTEED WORSE CASE



SIEMON TYPICAL

Frequency (MHz)	Insertion Loss (dB)		NEXT (dB)		PSNEXT (dB)		ACR (dB)		PSACR (dB)		ACR-F (dB)		PSACR-F (dB)		Return Loss (dB)		Propagation Delay (ns)	
	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical
1	2.1	1.8	75.3	93.5	73.3	92.7	73.2	93.1	71.2	90.9	73.3	97.1	71.3	93.7	20.0	23.9	570.0	448
4	3.8	3.6	66.3	98.3	64.3	95.9	62.5	94.7	60.5	92.4	61.3	96.4	59.3	93.9	23.0	27.3	552.0	442
10	5.9	5.5	60.3	87.5	58.3	87.2	54.4	82.0	52.4	81.6	53.3	86.4	51.3	85.7	25.0	32.7	545.4	439
16	7.5	7.1	57.2	83.4	55.2	82.9	49.8	76.3	47.8	75.8	49.2	81.2	47.2	81.1	25.0	31.2	543.0	438
20	8.4	8.0	55.8	77.4	53.8	76.7	47.4	69.4	45.4	68.7	47.3	75.0	45.3	74.4	25.0	32.4	542.0	437
31.25	10.5	10.1	52.9	81.1	50.9	80.4	42.4	71.0	40.4	70.3	43.4	73.5	41.4	73.1	23.6	30.0	540.4	436
62.5	15.0	14.3	48.4	87.1	46.4	84.1	33.4	72.7	31.4	69.8	37.4	74.2	35.4	73.1	21.5	31.8	538.6	435
100	19.1	18.2	45.3	80.6	43.3	79.4	26.2	62.3	24.2	61.1	33.3	68.3	31.3	66.8	20.1	31.3	537.6	435
200	27.6	25.8	40.8	74.4	38.8	71.2	13.2	48.5	11.2	45.4	27.3	63.9	25.3	62.4	18.0	31.3	536.5	434
250	31.1	28.9	39.3	74.4	37.3	7.8	8.3	45.9	6.3	42.7	25.3	61.0	23.3	59.5	17.3	29.5	536.3	434
300	34.3	31.9	38.1	72.5	36.1	69.8	3.9	41.9	1.9	37.8	23.8	62.0	21.8	60.3	17.3	26.2	536.1	434
400	40.1	37.2	36.3	68.9	34.3	65.7	-3.8	31.7	-5.8	28.4	21.3	54.6	19.3	52.3	17.3	26.2	535.8	434
500	45.3	41.6	34.8	65.9	32.8	64.0	-10.4	23.9	-12.4	22.1	19.3	55.9	17.3	53.8	17.3	28.0	535.6	434
550*	-	44.0	-	58.2	-	54.9	-	14.0	-	10.4	-	41.5	-	40.4	-	20.3	-	434
625*	-	46.2	-	57.6	-	56.5	-	11.2	-	9.3	-	41.5	-	39.8	-	22.6	-	434
750*	-	51.9	-	58.6	-	56.0	-	6.6	-	4.2	-	42.6	-	40.4	-	19.2	-	434

*Values for frequencies beyond 500 mHz are for information only.

All performance based on 100 metres (328 ft.).

Ordering Information:

Part #	Description
9N6L4-A5.	Category 6A F/FTP cable, LSOH, violet jacket, 305m (1000 ft.)