

# IC<sup>®</sup> 6 Modular Cords - US

Siemon's category 6 IC solid single-ended modular cords are designed for use in category 6 applications requiring a consolidation point (CP) or cross-connect (as an equipment cord). The cords are 100% factory transmission tested to 250 MHz and feature the same plug construction used in Siemon's stranded category 6 modular cords. These cords are available in CMP and CMR versions and are single-ended for direct termination.

Double and single-end versions available both in T568A and T568B wiring schemes

All Siemon factory assembled cords are 100% tested to 250 MHz

Slide on strain relief boots feature a latch guard to protect plug latch from snagging when pulling cords through pathways or cable managers

Modular plugs provide long-term resistance to corrosion from humidity, extreme temperatures, and airborne contaminants

Plug geometry meets ANSI/TIA -1096-A, IEC 60603-7, and TIA 1096-A specifications for modular plugs

Patented metallic isolator shields pairs inside plug for optimum NEXT performance

Note: IC 6 modular cords are backward compatible with all Siemon lower category-rated outlets. For example, when IC 6 modular cords are used in a System 5e<sup>®</sup> channel with Siemon category 5e outlets, we guarantee category 5e system performance. Reference Siemon ITR-981124-906 for more information

Strain and bend relief provides improved plug-to-cable retention and maximum performance by preventing pair deformation, as caused by mechanical strain

# PRODUCT INFORMATION

ELECTRICAL	
Contact Resistance	20 mΩ
Input to Output DC Resistance	200 mΩ
Min. Dielectric Withstand Voltage (contact to contact)	1000 V DC or AC peak
Insulation Resistance	500 mΩ
Compatibility	Backwards to cat 5e
Current Rating @ 25° C	1.5 A
Power over Ethernet	Suitable for PoE and PoE+
MECHANICAL — GENERAL	
Operating Temperature	-10 to 60 °C, (14 to 140 °F)
Flammability Rating	UL 94 - V0
Green Features	RoHS, lead-free, halogen-free, PVC free
Contact Materials	copper alloy
Plastic Materials	Flame retardant thermoplastic
Marking	P/N, length, performance level, QC
MECHANICAL — PLUG	
Number of Plug Insertion Cycles	750
Min. Plug Retention Force	50N
Plug Compatibility	Compatible with RJ45 outlets

\*Refer to Siemon Cable spec sheets for additional performance, electrical and mechanical information.

## Premium 6 IC Modular Cords

Part #	Description
IC6E-8A-(XX)-B(XX)R(X) . . . . .	Premium 6 IC, non-plenum, 4-pair UTP 23 AWG solid, modular cord, blue jacket with colored boot, T568B, CMR
IC6E-8T-(XX)-B(XX)R(X) . . . . .	Premium 6 IC, non-plenum, 4-pair UTP 23 AWG solid, modular cord, blue jacket with colored boot, T568A, CMR
IC6E-8A-(XX)-B(XX)P(X) . . . . .	Premium 6 IC, plenum, 4-pair UTP 23 AWG solid, modular cord, blue jacket with colored boot T568B, CMP
IC6E-8T-(XX)-B(XX)P(X) . . . . .	Premium 6 IC, plenum, 4-pair UTP 23 AWG solid, modular cord, blue jacket with colored boot, T568A, CMP

## System 6 IC Modular Cords

Part #	Description
IC6-8A-(XX)-B(XX)R(X) . . . . .	System 6 IC, non-plenum, 4-pair UTP 23 AWG solid, modular cord, blue jacket with colored boot, T568B, CMR
IC6-8T-(XX)-B(XX)R(X) . . . . .	System 6 IC, non-plenum, 4-pair UTP 23 AWG solid, modular cord, blue jacket with colored boot, T568A, CMR
IC6-8A-(XX)-B(XX)P(X) . . . . .	System 6 IC, plenum, 4-pair UTP 23 AWG solid, modular cord, blue jacket with colored boot T568B, CMP
IC6-8T-(XX)-B(XX)P(X) . . . . .	System 6 IC, plenum, 4-pair UTP 23 AWG solid, modular cord, blue jacket with colored boot, T568A, CMP

Use 1st (XX) to specify cord length: 10 = 3.1m (10 ft.), 20 = 6.1m (20 ft.), 30 = 9.1m (30 ft.), 40 = 12.2m (40 ft.), 50 = 15.2m (50 ft.), 60 = 18.3m (60 ft.)

Use 2nd (XX) to specify color of boot: 01 = black, 02 = white, 03 = red, 04 = gray, 05 = yellow, 06 = blue, 07 = green

Use (X) to specify single or double ended: Blank = single-ended, D = double-ended

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

IC® and Premium 6 are trademarks of Siemon

**Worldwide Headquarters**  
**North America**  
 Watertown, CT USA  
 Phone (1) 860 945 4200

**Regional Headquarters**  
**Europe Russia Africa**  
 Chertsy, Surrey, England  
 Phone (44) 0 1932 571771

**Regional Headquarters**  
**China**  
 Shanghai, P.R. China  
 Phone (86) 215385 0303

**Regional Headquarters**  
**Latin America**  
 Bogota, Colombia  
 Phone (571) 657 1950/51/52

**Regional Headquarters**  
**India Middle East**  
 Dubai, United Arab Emirates  
 Phone (971) 4 3689743

**Regional Headquarters**  
**Asia Pacific**  
 Sydney, Australia  
 Phone (86) 21 5385 0303

**Siemon Interconnect Solutions**  
**Watertown, CT USA**  
 Phone (1) 860 945 4213 US  
 www.siemon.com/SIS