


Category 7 600 MHz Cable - International

Siemon's Category 7 600 MHz cable perfectly complements the performance of our TERA outlets. Siemon cable exceeds all ISO/IEC requirements for category 7/class F transmission performance beyond 600 MHz. A fully shielded cable with individual foils around each pair coupled with an outer braid provides perfect immunity from outside interferences. In addition, the cable jacket has been qualified for mechanical reliability in high temperature environments up to 75°C. In PoE remote power applications, this cable can be installed in environments up to 60°C and will not experience degradation due to heat rise inside the cable bundle. Siemon cable is the ideal way to ensure optimum channel performance and is essential for a complete end-to-end warranted solution.

CABLE — INTERNATIONAL



COMPLIANCE

- ISO/IEC 11801: Ed 2.2 (Class F)
- IEC 61156-5 Ed 2.1 (Category 7)
- EN 50288 • EN 55022
- EN 50173 • EN 55024
- LSOH: IEC 60332-1, IEC 60754, and IEC 61034
- EN 50399 Class C_{ca}S_{1a}d_{1a}1*

CABLE CONSTRUCTION

- S/FTP
- Nominal jacket OD: 7.1mm (0.28 in.)
- 0.56mm (0.022 in.) solid (non-tinned) copper
- Reverse sequential measurement markings
- Pairs individually shielded
- Overall tinned-copper braid

ELECTRICAL SPECIFICATIONS (Nominal)

DC Resistance	<7.32 Ω/100m
DC Resistance Unbalance	2%
Mutual Capacitance	5.6 nF/100m
Capacitance Unbalance	<160 pF/100m
Characteristic Impedance (ohms)	1-100 MHz: 100 ± 15% 100-600 MHz: 100 ± 22%
NVP	72%
TCL	40-10 x log(f)dB
Delay Skew	≤25ns/100m

PHYSICAL PROPERTIES

	LSOH
Pulling Tension (max)	80N (18 lbf)
Bend Radius (min)	50mm (2.0 in.)
Installation Temperature	0 to 75°C (+32 to 167°F)
Storage Temperature	-20 to 75°C (-4 to 167°F)
Operating Temperature	-20 to 75°C (-4 to 167°F)

TRANSMISSION PERFORMANCE

GUARANTEED WORST CASE
 SIEMON TYPICAL

Frequency (MHz)	Insertion Loss (dB)		NEXT (dB)		PS NEXT (dB)		ACR (dB)		PSACR (dB)		ACR-F (dB)		PS ACR-F (dB)		Return Loss (dB)	
	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical
1.0	2.1	1.8	78.0	103.7	75.0	110.0	75.9	101.9	72.9	108.2	78.0	94.8	75.0	102.3	20.0	32.7
4.0	3.7	3.4	78.0	106.8	75.0	117.2	74.3	103.4	71.3	113.8	78.0	90.5	75.0	91.8	23.0	27.4
10.0	5.8	5.3	78.0	111.6	75.0	121.1	72.2	106.3	69.2	115.8	78.0	109.0	75.0	116.2	25.0	35.9
16.0	7.3	6.8	78.0	113.9	75.0	121.9	70.7	107.0	67.7	115.1	78.0	107.0	75.0	114.5	25.0	36.6
20.0	8.2	7.6	78.0	110.2	75.0	117.4	69.8	102.5	66.8	109.7	78.0	115.7	75.0	117.7	25.0	36.4
31.25	10.3	9.7	78.0	112.4	75.0	119.5	67.7	102.7	64.7	109.8	75.4	106.8	72.4	109.8	23.6	39.2
62.5	14.6	13.9	78.0	114.0	75.0	121.6	63.4	100.1	60.4	107.7	69.4	102.4	66.4	109.8	21.5	33.6
100.0	18.5	17.7	78.0	108.3	75.0	117.5	59.5	90.6	56.5	99.8	65.3	100.8	62.3	103.0	20.1	37.8
200.0	26.5	25.2	73.9	112.5	70.9	118.7	47.4	87.3	44.4	93.6	59.3	85.9	56.3	90.9	18.0	38.9
250.0	29.7	28.3	72.4	108.6	69.4	115.0	42.7	80.3	39.7	86.8	57.3	88.2	54.3	89.5	17.3	35.2
300.0	32.7	31.1	71.2	106.2	68.2	112.2	38.6	75.1	35.6	81.1	55.8	84.7	52.8	90.1	17.3	36.9
400.0	38.0	36.1	69.4	108.0	66.4	116.9	31.4	71.9	28.4	80.8	53.3	71.9	50.3	76.8	17.3	36.2
500.0	42.8	40.4	67.9	96.1	64.9	103.4	25.2	55.7	22.2	62.9	51.3	79.6	48.3	83.6	17.3	32.8
600.0	47.1	44.4	66.7	97.0	63.7	101.8	19.6	52.5	16.6	57.4	49.7	69.9	46.7	71.7	17.3	34.8
700.0*	-	48.2	-	98.8	-	106.0	-	50.6	-	57.8	-	59.9	-	61.0	-	33.5
800.0*	-	51.8	-	94.6	-	103.7	-	42.8	-	51.9	-	60.9	-	62.9	-	29.9
850.0*	-	53.9	-	82.2	-	94.7	-	28.4	-	40.8	-	48.1	-	55.2	-	31.0

*Values above 600 MHz are for information only.

Ordering Information:

Part #	Description
9T7L4-E6.....	LSOH (IEC 60332-1), violet jacket, Class E _{ca} , D _{ca} , C _{ca} *, 305m (1000 ft.)
9T7L4-E6-5CR.....	LSOH (IEC 60332-1), violet jacket, Class E _{ca} , D _{ca} , C _{ca} *, 500m (1640 ft.)
9T7L4-E6-1KR.....	LSOH (IEC 60332-1), violet jacket, Class E _{ca} , D _{ca} , C _{ca} *, 1000m (3281 ft.)

*Initial type test complete. System 1+ requirements pending

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

Worldwide Headquarters
North America
 Watertown, CT USA
 Phone (1) 860 945 4200

Regional Headquarters
Europe Russia Africa
 Chertsy, Surrey, England
 Phone (44) 0 1932 571771

Regional Headquarters
China
 Shanghai, P.R. China
 Phone (86) 215385 0303

Regional Headquarters
Latin America
 Bogota, Colombia
 Phone (571) 657 1950/51/52

Regional Headquarters
India Middle East
 Dubai, United Arab Emirates
 Phone (971) 4 3689743

Regional Headquarters
Asia Pacific
 Sydney, Australia
 Phone (86) 21 5385 0303

Siemon Interconnect Solutions
Watertown, CT USA
 Phone (1) 860 945 4213 US
 www.siemon.com/SIS