

XGLO® & LightSystem® Indoor/Outdoor LooseTube, Eca - EMEA


Siemon LSOH (IEC 60332-1) indoor/outdoor loose tube cables are ideal for campus and building backbones. Siemon fiber optic cables are offered in XGLO and LightSystem configurations supporting high-speed, applications such as Gigabit Ethernet, 10 Gigabit Ethernet and Fiber Channel. Siemon indoor/outdoor water blocking is primarily for dry duct applications for moisture and temporary water migration protection.

Ordering Information:

9GG(X)L(XXXX)-(XXXX)M LightSystem Multimode 62.5/125 OM1, XGLO Multimode 50/125 OM3, 50/125 OM4, Singlemode

Fiber Type	Length	Performance
6 = 62.5/125µm	M = Meters	G106 = OM1 62.5/125µm, Blue
5 = 50/125µm		T306 = OM3 50/125µm Laser Optimised, Blue
8 = OS1/OS2 Singlemode		T506 = OM4 50/125µm Laser Optimised, Blue
		T516 = OM4 50/125µm Laser Optimised, Erika Violet
		E206 = OS1/OS2 Singlemode, Blue

Cable Rating	Fiber Count (Subunit)	Fiber Count (Subunit)
L = LSOH - 1	002B = 2 (1 Tube with 2 Fibers)	024D = 24 (4 Tubes with 6 Fibers)
	004C = 4 (1 Tube with 4 Fibers)	036G = 36 (6 Tubes with 6 Fibers)
	006D = 6 (1 Tube with 6 Fibers)	048G = 48 (4 Tubes with 12 Fibers)
	008E = 8 (1 Tube with 8 Fibers)	072G = 72 (6 Tubes with 12 Fibers)
	012G = 12 (1 Tube with 12 Fibers)	096G = 96 (8 Tubes with 12 Fibers)
	016D = 16 (2 Tubes with 6 Fibers, 1 Tube with 4 Fibers)	144G = 144 (12 Tubes with 12 Fibers)



Note: The 2-12 strand rodent resistant cables feature a glass yarn design with a high tensile strength and degree of rodent protection which is effective in many cases. The function of glass yarns differs from the other rodent protection materials such as a 100% metallic armour protection. The glass yarns provide a degree of protection because it is disagreeable and unpleasant for most rodents to gnaw the glass yarns.

LIGHTSYSTEM Multimode, 62.5/125, OM1	XGLO 300 Multimode, 50/125, OM3	XGLO 550 Multimode, 50/125, OM4	XGLO Singlemode, OS1/OS2																																																																																				
STANDARDS COMPLIANCE <ul style="list-style-type: none"> ISO/IEC 11801:2002 OM1 (62.5/125) ANSI/TIA-568.3-D ANSI/TIA-598-D ANSI/TIA-492 AAAA Telcordia GR-409-CORE IEC 60332-1-2 (Single strand) IEC 60754-1-2 (Non Halogens) IEC 60754-2 (Acid gas) IEC 61034-2 (Smoke density) EN 60332-1-2 Class Eco 	STANDARDS COMPLIANCE <ul style="list-style-type: none"> ISO/IEC 11801:2002 OM3 ANSI/TIA-568.3-D ANSI/TIA-598-D ANSI/TIA-492 AAAC IEC 60793-2-10 Fiber Type A1a.2 Telcordia GR-409-CORE IEC 60332-1-2 (Single strand) IEC 60754-1-2 (Non Halogens) IEC 60754-2 (Acid gas) IEC 61034-2 (Smoke density) EN 60332-1-2 Class Eco 	STANDARDS COMPLIANCE <ul style="list-style-type: none"> ISO/IEC 11801:2002 OM3 ISO/IEC 11801:2002 Amendment 2 OM4 ANSI/TIA-568.3-D ANSI/TIA-598-D ANSI/TIA-492 CAAB ANSI/TIA-492 AAAD IEC 60793-2-10 Fiber Type A1a.3 Telcordia GR-409-CORE IEC 60332-1-2 (Single strand) IEC 60754-1-2 (Non Halogens) IEC 60754-2 (Acid gas) IEC 61034-2 (Smoke density) EN 60332-1-2 Class Eco 	STANDARDS COMPLIANCE <ul style="list-style-type: none"> ISO/IEC 11801:Ed 2.0 Amendment:1:2008 ANSI/TIA-568.3-D ANSI/TIA-598-D ANSI/TIA-492 CAAB Telcordia GR-409-CORE ITU-T G.652 C/D IEC 60332-1-2 (Single strand) IEC 60754-1-2 (Non Halogens) IEC 60754-2 (Acid gas) IEC 61034-2 (Smoke density) EN 60332-1-2 Class Eco 																																																																																				
APPLICATIONS SUPPORT <table border="1"> <thead> <tr> <th>APPLICATION</th> <th>DISTANCE (m)</th> </tr> </thead> <tbody> <tr><td>10 GBASE-S (850 nm)</td><td>N/A</td></tr> <tr><td>62.5/125µm</td><td>26</td></tr> <tr><td>1000 BASE-S (850 nm)</td><td>N/A</td></tr> <tr><td>62.5/125µm</td><td>275</td></tr> <tr><td>1000BASE-LX (1300 nm)</td><td>550</td></tr> <tr><td>Fiber Channel 266 (1300 nm)</td><td>1,500</td></tr> <tr><td>ATM 622 (1300 nm)</td><td>500</td></tr> <tr><td>ATM 155 (1300 nm)</td><td>2,000</td></tr> <tr><td>ATM 52 (1300 nm)</td><td>3,000</td></tr> <tr><td>FDD1 (Original-1300 nm)</td><td>2,000</td></tr> <tr><td>100BASE-FX (1300 nm)</td><td>2,000</td></tr> </tbody> </table>	APPLICATION	DISTANCE (m)	10 GBASE-S (850 nm)	N/A	62.5/125µm	26	1000 BASE-S (850 nm)	N/A	62.5/125µm	275	1000BASE-LX (1300 nm)	550	Fiber Channel 266 (1300 nm)	1,500	ATM 622 (1300 nm)	500	ATM 155 (1300 nm)	2,000	ATM 52 (1300 nm)	3,000	FDD1 (Original-1300 nm)	2,000	100BASE-FX (1300 nm)	2,000	APPLICATIONS SUPPORT <table border="1"> <thead> <tr> <th>APPLICATION</th> <th>DISTANCE (m)</th> </tr> </thead> <tbody> <tr><td>10 GBASE-S (850 nm)</td><td>300</td></tr> <tr><td>10 GBASE-LX4 (1300 nm)</td><td>300</td></tr> <tr><td>1000BASE-S (850 nm)</td><td>1000</td></tr> <tr><td>1000 BASE-LX (1300 nm)</td><td>600</td></tr> <tr><td>Fiber Channel 266 (1300 nm)</td><td>1,500</td></tr> <tr><td>ATM 622 (1300 nm)</td><td>500</td></tr> <tr><td>ATM 155 (1300 nm)</td><td>2,000</td></tr> <tr><td>ATM 52 (1300 nm)</td><td>3,000</td></tr> <tr><td>FDD1 (Original-1300 nm)</td><td>2,000</td></tr> <tr><td>100BASE-FX (1300 nm)</td><td>2,000</td></tr> </tbody> </table>	APPLICATION	DISTANCE (m)	10 GBASE-S (850 nm)	300	10 GBASE-LX4 (1300 nm)	300	1000BASE-S (850 nm)	1000	1000 BASE-LX (1300 nm)	600	Fiber Channel 266 (1300 nm)	1,500	ATM 622 (1300 nm)	500	ATM 155 (1300 nm)	2,000	ATM 52 (1300 nm)	3,000	FDD1 (Original-1300 nm)	2,000	100BASE-FX (1300 nm)	2,000	APPLICATIONS SUPPORT <table border="1"> <thead> <tr> <th>APPLICATION</th> <th>DISTANCE (m)</th> </tr> </thead> <tbody> <tr><td>10GBASE-S (850 nm)</td><td>550</td></tr> <tr><td>10GBASE-LX4 (1300 nm)</td><td>300</td></tr> <tr><td>1000BASE-S (850 nm)</td><td>1100</td></tr> <tr><td>1000BASE-LX (1300 nm)</td><td>600</td></tr> <tr><td>Fiber Channel 266 (1300 nm)</td><td>1,500</td></tr> <tr><td>ATM 622 (1300 nm)</td><td>500</td></tr> <tr><td>ATM 155 (1300 nm)</td><td>2,000</td></tr> <tr><td>ATM 52 (1300 nm)</td><td>3,000</td></tr> <tr><td>FDD1 (Original-1300 nm)</td><td>2,000</td></tr> <tr><td>100BASE-FX (1300 nm)</td><td>2,000</td></tr> </tbody> </table>	APPLICATION	DISTANCE (m)	10GBASE-S (850 nm)	550	10GBASE-LX4 (1300 nm)	300	1000BASE-S (850 nm)	1100	1000BASE-LX (1300 nm)	600	Fiber Channel 266 (1300 nm)	1,500	ATM 622 (1300 nm)	500	ATM 155 (1300 nm)	2,000	ATM 52 (1300 nm)	3,000	FDD1 (Original-1300 nm)	2,000	100BASE-FX (1300 nm)	2,000	APPLICATIONS SUPPORT <table border="1"> <thead> <tr> <th>APPLICATION</th> <th>DISTANCE (m)</th> </tr> </thead> <tbody> <tr><td>10GBASE-L (1310 nm)</td><td>8,000</td></tr> <tr><td>10GBASE-E (1550 nm)</td><td>30,000</td></tr> <tr><td>10G Fiber Channel (Serial-1310 nm)</td><td>10,000</td></tr> <tr><td>10G Fiber Channel (WDM-1310 nm)</td><td>10,000</td></tr> <tr><td>1000BASE-LX (1300 nm)</td><td>5,000</td></tr> <tr><td>Fiber Channel 266/1062 (1300 nm)</td><td>10,000</td></tr> <tr><td>ATM 52/155/622 (1300 nm)</td><td>15,000</td></tr> </tbody> </table>	APPLICATION	DISTANCE (m)	10GBASE-L (1310 nm)	8,000	10GBASE-E (1550 nm)	30,000	10G Fiber Channel (Serial-1310 nm)	10,000	10G Fiber Channel (WDM-1310 nm)	10,000	1000BASE-LX (1300 nm)	5,000	Fiber Channel 266/1062 (1300 nm)	10,000	ATM 52/155/622 (1300 nm)	15,000
APPLICATION	DISTANCE (m)																																																																																						
10 GBASE-S (850 nm)	N/A																																																																																						
62.5/125µm	26																																																																																						
1000 BASE-S (850 nm)	N/A																																																																																						
62.5/125µm	275																																																																																						
1000BASE-LX (1300 nm)	550																																																																																						
Fiber Channel 266 (1300 nm)	1,500																																																																																						
ATM 622 (1300 nm)	500																																																																																						
ATM 155 (1300 nm)	2,000																																																																																						
ATM 52 (1300 nm)	3,000																																																																																						
FDD1 (Original-1300 nm)	2,000																																																																																						
100BASE-FX (1300 nm)	2,000																																																																																						
APPLICATION	DISTANCE (m)																																																																																						
10 GBASE-S (850 nm)	300																																																																																						
10 GBASE-LX4 (1300 nm)	300																																																																																						
1000BASE-S (850 nm)	1000																																																																																						
1000 BASE-LX (1300 nm)	600																																																																																						
Fiber Channel 266 (1300 nm)	1,500																																																																																						
ATM 622 (1300 nm)	500																																																																																						
ATM 155 (1300 nm)	2,000																																																																																						
ATM 52 (1300 nm)	3,000																																																																																						
FDD1 (Original-1300 nm)	2,000																																																																																						
100BASE-FX (1300 nm)	2,000																																																																																						
APPLICATION	DISTANCE (m)																																																																																						
10GBASE-S (850 nm)	550																																																																																						
10GBASE-LX4 (1300 nm)	300																																																																																						
1000BASE-S (850 nm)	1100																																																																																						
1000BASE-LX (1300 nm)	600																																																																																						
Fiber Channel 266 (1300 nm)	1,500																																																																																						
ATM 622 (1300 nm)	500																																																																																						
ATM 155 (1300 nm)	2,000																																																																																						
ATM 52 (1300 nm)	3,000																																																																																						
FDD1 (Original-1300 nm)	2,000																																																																																						
100BASE-FX (1300 nm)	2,000																																																																																						
APPLICATION	DISTANCE (m)																																																																																						
10GBASE-L (1310 nm)	8,000																																																																																						
10GBASE-E (1550 nm)	30,000																																																																																						
10G Fiber Channel (Serial-1310 nm)	10,000																																																																																						
10G Fiber Channel (WDM-1310 nm)	10,000																																																																																						
1000BASE-LX (1300 nm)	5,000																																																																																						
Fiber Channel 266/1062 (1300 nm)	10,000																																																																																						
ATM 52/155/622 (1300 nm)	15,000																																																																																						

XGLO® & LightSystem® Indoor/Outdoor LooseTube, Eca - EMEA

LightSystem Gigabit Ethernet Fiber Optic Cable

Minimum Performance Parameters for LightSystem 62.5/125µm Multimode Fiber

Fiber Type	Wavelength nm	Maximum Attenuation (dB/km)	Minimum Modal Bandwidth (MHz·km)	Guaranteed Gigabit Transmission Distance Meters (Feet)
62.5/125 (OM1)	850	3.5	200	275 (902)
	1300	1.0	500	550 (1804)

*The protocol pertinent to the transmission distance as noted is Gigabit Ethernet per IEEE 802.3:2005.

Minimum Performance Parameters for XGLO 50/125µm Multimode Fiber

Fiber Type	Guaranteed Gigabit Transmission Distance (m)		Guaranteed 10 Gigabit Transmission Distance (m)		Minimum Bandwidth (MHz·km)		Maximum Attenuation (dB/km)	
	850 nm	1300 nm	850 nm†	1300 nm††	850 nm	1300 nm	850 nm	1300 nm
50/125 (OM3)	1000	600	300	300	RML - 2000 OFL - 1500	OFL - 500	3.0	1.0
50/125 (OM4)	1100	600	550	300	RML - 4700 OFL - 3500	OFL - 500	3.0	1.0

† 10GBASE-S †† 10GBASE-LX4

Minimum Performance Parameters for XGLO Singlemode Fiber

Fiber Type	Wavelength (nm)	Maximum Attenuation (dB/km)
Singlemode (OS1/OS2)	1310	0.40
	1550	0.30

XGLO and LightSystem Indoor/Outdoor LooseTube (EMEA) Physical Specifications

PHYSICAL SPECIFICATIONS (All Values Are Nominal)

Fiber Count	Nominal Cable Diameter mm	Maximum Pulling Tension Newtons		Nominal Net Weight kg/km
		Installation	Long Term	
2	7.5	1500	700	55
4	7.5	1500	700	55
6	7.5	1500	700	55
8	7.5	1500	700	55
12	7.5	1500	700	55
16	10.5	1800	1200	90
24	10.5	1800	1200	90
36	10.5	1800	1200	90
48	10.5	1800	1200	90
72	10.5	1800	1200	90
96	12.0	1800	1200	125
144	15.0	1800	1200	190

Fiber Count	Maximum Crush Resistance (N/mm)	Operation Temperature °C (°F)	Installation Temperature °C (°F)	Storage Temperature °C (°F)	Minimum Bend Radius	
					Installation	Long Term
2-12	20	-20 to 70 (-4 to 158)	-20 to 70 (-14 to 158)	-40 to 70 (-40 to 158)	20 x DIA.	10 x DIA.
16-144	30	-20 to 70 (-4 to 158)	-20 to 70 (-4 to 158)	-40 to 70 (-40 to 158)	20 x DIA.	10 x DIA.

Custom lengths and jacket colours are available upon request. Contact our Customer Service Department for more information.