


XGLO® & LightSystem® Indoor/Outdoor Tight Buffer, C_{ca}s_{1a}, d₁, a₁ - EMEA


Siemon LSOH-FR indoor/outdoor tight buffer fiber cables are ideal for data centres, campus and building backbones. Siemon fiber optic cables are offered in XGLO and LightSystem configurations supporting high-speed applications such as Gigabit Ethernet, 10 Gigabit Ethernet and Fiber Channel. Siemon indoor/outdoor water blocking is primarily for dry duct applications for moisture and temporary water migration protection.

Ordering Information:



Fiber Count (Subunit)

- 002B = 2 (1 Tube with 2 Fibers)
- 004C = 4 (1 Tube with 4 Fibers)
- 006D = 6 (1 Tube with 6 Fibers)
- 008E = 8 (1 Tube with 8 Fibers)
- 012G = 12 (1 Tube with 12 Fibers)
- 016K = 16 (1 Tube with 16 Fibers)
- 024L = 24 (1 Tube with 24 Fibers)



2 - 24 Strands

LightSystem Multimode 62.5/125, OM1	XGLO 300 Multimode 50/125, OM3	XGLO 550 Multimode 50/125, OM4	XGLO Singlemode, OS1/OS2																																																																																				
STANDARDS COMPLIANCE <ul style="list-style-type: none"> • ISO/IEC 11801:2002 OM1 (62.5/125) • ANSI/TIA-568.3-D • ANSI/TIA-598-D • ANSI/TIA-492 AAAA • Telcordia GR-409-CORE • IEC 60332-1-2 • IEC 60332-3, IEC 60332-1-12 (Single strand), IEC 60754-2 (Acid gas), IEC 61034-2 (Smoke Density) • EN 50399 Class E_{ca}, D_{ca} Class C_{ca} S_{1a}, d₁, a₁ 	STANDARDS COMPLIANCE <ul style="list-style-type: none"> • ISO/IEC 11801:2002 OM3 • ANSI/TIA-568.3-D • ANSI/TIA-598-D • ANSI/TIA-492 AAAC • IEC 60793-2-10 Fiber Type A1a.2 • Telcordia GR-409-CORE • IEC 60332-1-2 • IEC 60332-3, IEC 60332-1-12 (Single strand), IEC 60754-2 (Acid gas), IEC 61034-2 (Smoke Density) • EN 50399 Class E_{ca}, D_{ca} Class C_{ca} S_{1a}, d₁, a₁ 	STANDARDS COMPLIANCE <ul style="list-style-type: none"> • ISO/IEC 11801:2002 OM3 • ISO/IEC 11801:2002 Amendment 2 OM4 • ANSI/TIA-568.3-D • ANSI/TIA-598-D • ANSI/TIA-492 AAAD • IEC 60793-2-10 Fiber Type A1a.3 • Telcordia GR-409-CORE • IEC 60332-1-2 • IEC 60332-3, IEC 60332-1-12 (Single strand), IEC 60754-2 (Acid gas), IEC 61034-2 (Smoke Density) • EN 50399 Class E_{ca}, D_{ca} Class C_{ca} S_{1a}, d₁, a₁ 	STANDARDS COMPLIANCE <ul style="list-style-type: none"> • ISO/IEC 11801:Ed 2.0 Amendment:1:2008 • ANSI/TIA-568.3-D • ANSI/TIA-598-D • ANSI/TIA-492 CAAB • Telcordia GR-409-CORE • ITU-T G.652 C/D • IEC 60332-1-2, Class • IEC 60332-3, IEC 60332-1-12 (Single strand), IEC 60754-2 (Acid gas), IEC 61034-2 (Smoke Density) • EN 50399 Class E_{ca}, D_{ca} Class C_{ca} S_{1a}, d₁, a₁ 																																																																																				
APPLICATIONS SUPPORT <table border="1"> <thead> <tr> <th>APPLICATION</th> <th>DISTANCE (m)</th> </tr> </thead> <tbody> <tr><td>10GBASE-S (850 nm)</td><td>N/A</td></tr> <tr><td>62.5/125µm</td><td>26</td></tr> <tr><td>1000BASE-S (850 nm)</td><td>N/A</td></tr> <tr><td>62.5/125µm</td><td>275</td></tr> <tr><td>1000BASE-LX (1300 nm)</td><td>550</td></tr> <tr><td>Fiber Channel 266 (1300 nm)</td><td>1,500</td></tr> <tr><td>ATM 622 (1300 nm)</td><td>500</td></tr> <tr><td>ATM 155 (1300 nm)</td><td>2,000</td></tr> <tr><td>ATM 52 (1300 nm)</td><td>3,000</td></tr> <tr><td>FDD1 (Original-1300 nm)</td><td>2,000</td></tr> <tr><td>100BASE-FX (1300 nm)</td><td>2,000</td></tr> </tbody> </table>	APPLICATION	DISTANCE (m)	10GBASE-S (850 nm)	N/A	62.5/125µm	26	1000BASE-S (850 nm)	N/A	62.5/125µm	275	1000BASE-LX (1300 nm)	550	Fiber Channel 266 (1300 nm)	1,500	ATM 622 (1300 nm)	500	ATM 155 (1300 nm)	2,000	ATM 52 (1300 nm)	3,000	FDD1 (Original-1300 nm)	2,000	100BASE-FX (1300 nm)	2,000	APPLICATIONS SUPPORT <table border="1"> <thead> <tr> <th>APPLICATION</th> <th>DISTANCE (m)</th> </tr> </thead> <tbody> <tr><td>10GBASE-S (850 nm)</td><td>300</td></tr> <tr><td>10GBASE-LX4 (1300 nm)</td><td>300</td></tr> <tr><td>1000BASE-S (850 nm)</td><td>1000</td></tr> <tr><td>1000BASE-LX (1300 nm)</td><td>600</td></tr> <tr><td>Fiber Channel 266 (1300 nm)</td><td>1,500</td></tr> <tr><td>ATM 622 (1300 nm)</td><td>500</td></tr> <tr><td>ATM 155 (1300 nm)</td><td>2,000</td></tr> <tr><td>ATM 52 (1300 nm)</td><td>3,000</td></tr> <tr><td>FDD1 (Original-1300 nm)</td><td>2,000</td></tr> <tr><td>100BASE-FX (1300 nm)</td><td>2,000</td></tr> </tbody> </table>	APPLICATION	DISTANCE (m)	10GBASE-S (850 nm)	300	10GBASE-LX4 (1300 nm)	300	1000BASE-S (850 nm)	1000	1000BASE-LX (1300 nm)	600	Fiber Channel 266 (1300 nm)	1,500	ATM 622 (1300 nm)	500	ATM 155 (1300 nm)	2,000	ATM 52 (1300 nm)	3,000	FDD1 (Original-1300 nm)	2,000	100BASE-FX (1300 nm)	2,000	APPLICATIONS SUPPORT <table border="1"> <thead> <tr> <th>APPLICATION</th> <th>DISTANCE (m)</th> </tr> </thead> <tbody> <tr><td>10GBASE-S (850 nm)</td><td>550</td></tr> <tr><td>10GBASE-LX4 (1300 nm)</td><td>300</td></tr> <tr><td>1000BASE-S (850 nm)</td><td>1100</td></tr> <tr><td>1000BASE-LX (1300 nm)</td><td>600</td></tr> <tr><td>Fiber Channel 266 (1300 nm)</td><td>1,500</td></tr> <tr><td>ATM 622 (1300 nm)</td><td>500</td></tr> <tr><td>ATM 155 (1300 nm)</td><td>2,000</td></tr> <tr><td>ATM 52 (1300 nm)</td><td>3,000</td></tr> <tr><td>FDD1 (Original-1300 nm)</td><td>2,000</td></tr> <tr><td>100BASE-FX (1300 nm)</td><td>2,000</td></tr> </tbody> </table>	APPLICATION	DISTANCE (m)	10GBASE-S (850 nm)	550	10GBASE-LX4 (1300 nm)	300	1000BASE-S (850 nm)	1100	1000BASE-LX (1300 nm)	600	Fiber Channel 266 (1300 nm)	1,500	ATM 622 (1300 nm)	500	ATM 155 (1300 nm)	2,000	ATM 52 (1300 nm)	3,000	FDD1 (Original-1300 nm)	2,000	100BASE-FX (1300 nm)	2,000	APPLICATIONS SUPPORT <table border="1"> <thead> <tr> <th>APPLICATION</th> <th>DISTANCE (m)</th> </tr> </thead> <tbody> <tr><td>10GBASE-L (1310 nm)</td><td>8,000</td></tr> <tr><td>10GBASE-E (1550 nm)</td><td>30,000</td></tr> <tr><td>10G Fiber Channel (Serial-1310 nm)</td><td>10,000</td></tr> <tr><td>10G Fiber Channel (WDM-1310 nm)</td><td>10,000</td></tr> <tr><td>1000BASE-LX (1300 nm)</td><td>5,000</td></tr> <tr><td>Fiber Channel 266/1062 (1300 nm)</td><td>10,000</td></tr> <tr><td>ATM 52/155/622 (1300 nm)</td><td>15,000</td></tr> </tbody> </table>	APPLICATION	DISTANCE (m)	10GBASE-L (1310 nm)	8,000	10GBASE-E (1550 nm)	30,000	10G Fiber Channel (Serial-1310 nm)	10,000	10G Fiber Channel (WDM-1310 nm)	10,000	1000BASE-LX (1300 nm)	5,000	Fiber Channel 266/1062 (1300 nm)	10,000	ATM 52/155/622 (1300 nm)	15,000
APPLICATION	DISTANCE (m)																																																																																						
10GBASE-S (850 nm)	N/A																																																																																						
62.5/125µm	26																																																																																						
1000BASE-S (850 nm)	N/A																																																																																						
62.5/125µm	275																																																																																						
1000BASE-LX (1300 nm)	550																																																																																						
Fiber Channel 266 (1300 nm)	1,500																																																																																						
ATM 622 (1300 nm)	500																																																																																						
ATM 155 (1300 nm)	2,000																																																																																						
ATM 52 (1300 nm)	3,000																																																																																						
FDD1 (Original-1300 nm)	2,000																																																																																						
100BASE-FX (1300 nm)	2,000																																																																																						
APPLICATION	DISTANCE (m)																																																																																						
10GBASE-S (850 nm)	300																																																																																						
10GBASE-LX4 (1300 nm)	300																																																																																						
1000BASE-S (850 nm)	1000																																																																																						
1000BASE-LX (1300 nm)	600																																																																																						
Fiber Channel 266 (1300 nm)	1,500																																																																																						
ATM 622 (1300 nm)	500																																																																																						
ATM 155 (1300 nm)	2,000																																																																																						
ATM 52 (1300 nm)	3,000																																																																																						
FDD1 (Original-1300 nm)	2,000																																																																																						
100BASE-FX (1300 nm)	2,000																																																																																						
APPLICATION	DISTANCE (m)																																																																																						
10GBASE-S (850 nm)	550																																																																																						
10GBASE-LX4 (1300 nm)	300																																																																																						
1000BASE-S (850 nm)	1100																																																																																						
1000BASE-LX (1300 nm)	600																																																																																						
Fiber Channel 266 (1300 nm)	1,500																																																																																						
ATM 622 (1300 nm)	500																																																																																						
ATM 155 (1300 nm)	2,000																																																																																						
ATM 52 (1300 nm)	3,000																																																																																						
FDD1 (Original-1300 nm)	2,000																																																																																						
100BASE-FX (1300 nm)	2,000																																																																																						
APPLICATION	DISTANCE (m)																																																																																						
10GBASE-L (1310 nm)	8,000																																																																																						
10GBASE-E (1550 nm)	30,000																																																																																						
10G Fiber Channel (Serial-1310 nm)	10,000																																																																																						
10G Fiber Channel (WDM-1310 nm)	10,000																																																																																						
1000BASE-LX (1300 nm)	5,000																																																																																						
Fiber Channel 266/1062 (1300 nm)	10,000																																																																																						
ATM 52/155/622 (1300 nm)	15,000																																																																																						

XGLO® & LightSystem® Indoor/Outdoor Tight Buffer, C_{ca}s_{1a}, d₁, a₁ - EMEA

LightSystem Gigabit Ethernet Fiber Optic Cable

Minimum Performance Parameters for LightSystem 62.5/125µm Multimode Fiber

Fiber Type	Wavelength nm	Maximum Attenuation (dB/km)	Minimum Modal Bandwidth (MHz•km)	Guaranteed Gigabit Transmission Distance Meters (Feet)
62.5/125 (OM1)	850	3.5	200	275 (902)
	1300	1.0	500	550 (1804)

*The protocol pertinent to the transmission distance as noted is Gigabit Ethernet per IEEE 802.3:2005.

Minimum Performance Parameters for XGLO 50/125µm Multimode Fiber

Fiber Type	Guaranteed Gigabit Transmission Distance (m)		Guaranteed 10 Gigabit Transmission Distance (m)		Minimum Bandwidth (MHz•km)		Maximum Attenuation (dB/km)	
	850 nm	1300 nm	850 nm†	1300 nm††	850 nm	1300 nm	850 nm	1300 nm
50/125 (OM3)	1000	600	300	300	RML - 2000 OFL - 1500	OFL - 500	3.0	1.0
50/125 (OM4)	1100	600	550	300	RML - 4700 OFL - 3500	OFL - 500	3.0	1.0

† 10GBASE-S †† 10GBASE-LX4

Minimum Performance Parameters for XGLO Singlemode Fiber

Fiber Type	Wavelength (nm)	Maximum Attenuation (dB/km)
Singlemode (OS1/OS2)	1310	0.40
	1550	0.30

XGLO and LightSystem Indoor/Outdoor Tight Buffer (International) Physical Specifications

PHYSICAL SPECIFICATIONS (All Values Are Nominal)

Fiber Count	Nominal Cable Diameter (mm)	Maximum Pulling Tension Newtons (N)		Nominal Net Weight (kg/km)
		Installation	Long Term	
2	7.5	1500	1000	46
4	7.5	1500	1000	48
6	7.5	1500	1000	49
8	8.0	1500	1000	54
12	8.3	1500	1000	62
16	8.8	2100	1300	75
24	9.4	2400	1500	87

Fiber Count	Maximum Crush Resistance (N/mm)	Operation Temperature °C (°F)	Installation Temperature °C (°F)	Storage Temperature °C (°F)	Minimum Bend Radius	
					Installation	Long Term
2-24	25	-20 to 70 (-4 to 158)°F	-20 to 60 (-4 to 140)°F	-40 to 70 (-40 to 158)°F	20 x DIA.	10 x DIA.

Custom lengths and jacket colours are available upon request. Contact our Customer Service Department for more information.