



Z-MAX® 5e SHIELDED OUTLETS

Combining exceptional category 5e performance with best-in-class termination time, the Z-MAX 5e shielded outlet is a vital part of an end-to-end Z-MAX 5e shielded cabling system. The Z-MAX module exceeds all applicable industry standards, including ANSI/TIA-568-C.2 and Amendments 1 and 2 of ISO/IEC 11801 2nd ed.



User Friendly
The ergonomic and easy-to-use Z-TOOL ensures a fast, low force termination.



Flexibility and Simplified Ordering
Hybrid design allows the same outlet to be mounted in flat or angled orientations.



Seated contact position

Contact Integrity – Featuring Siemon's patented crowned jack contact geometry that improves electrical and mechanical performance and ensures that any jack or plug contact damage due to arcing caused by unmating under PoE load occurs well away from the final mated contact position.

STANDARDS COMPLIANCE

- ANSI/TIA-568-C.2
- ISO/IEC 11801 2nd ed Amendment 1
- ISO/IEC 11801 2nd ed Amendment 2
- IEEE 802.3an
- IEEE 802.3af (Type 1)
- IEEE 802.3at (Type 2)
- IEEE 802.3bt (Type 3 and 4)
- IEC 60603-7
- TIA-968-A (formerly FCC Part 68 Subpart F)

PRODUCT INFORMATION

Performance Specifications:

ELECTRICAL	
Contact Resistance	20 mΩ
Input to Output Resistance	200 mΩ
Min. Dielectric Withstand Voltage (contact to contact)	1000 AC peak
Min. Dielectric Withstand Voltage	1500 V DC (shield)
Insulation Resistance	500 mΩ
Current Rating	1.5 A
PoE	Suitable for PoE and PoE+
MECHANICAL – GENERAL	
Operating Temperature	-10 to 60 °C (14 to 140 °F)
Flammability Rating	UL 94 V-0
Green Features	RoHS, lead-free, halogen-free, PVC free
Housing Material	Zinc die cast
Contact Materials	Copper alloy, plated with 50 micro inches (1.27 micron) minimum thick gold or equivalent at contact interface
Plastic Materials	Flame retardant thermoplastic
Dimensions (LxWxH)	41.2x14.5x21.1mm (1.6x.570x.832 in.)
Shield	360 degree enclosure
MECHANICAL – JACK	
Number of Plug Insertion Cycles	2500
Min. Plug Retention Force	50N (11.24 lbf)
Plug Compatibility	Compatible with RJ45 (8-position) or RJ11 (6-position) plugs

MECHANICAL – TERMINATION	
Wire Size Range (nominal)	23-26 AWG solid and stranded *
Wire Insulation Diameter Range (max)	1.48mm (0.058 in.)
Conductor OD Size (max)	0.60mm (0.023 in.)
Cable OD (max)	9mm (0.354 in.)
Reterminations	5
Wiring	T568A/B

* Termination technique may vary. See product instructions

Each Z-MAX 6A hybrid outlet includes 1 printed icon set with the following color/print options.



- | | |
|-------------------------------|--------------------------------|
| 1 - Red Data | 1 - Red Voice |
| 1 - Blue Data | 1 - Blue Voice |
| 1 - Bezel Color-Matching Data | 1 - Bezel Color-Matching Voice |
| 1 - White Blank | 1 - Bezel Color-Matching Blank |



* Note: Keystone module not available with door

Ordering Information:

Z5-S(X)(XX)(X) Shielded Z-MAX Category 5e outlet, T568A/B

Mounting Style	Bezel Colour	Door Option
(Blank) = Hybrid Flat/Angled	01= Black 06= Blue	(Blank) = No Door
K = Keystone	02= White 07= Green	D = Spring Door (Hybrid only)
	03= Red 09= Orange	
	04= Grey 20= Ivory	
	05= Yellow 80= Light Ivory	

Outlet terminates S/FTP, F/FTP and F/UTP cable constructions with 22 – 26 AWG (0.64 – 0.51mm) solid and 26 AWG (0.48mm) stranded conductors, with up to 0.60mm diameter conductors and up to 1.48mm diameter over insulation.

ⓑ Add "B" to end of part number for bulk project pack of 100 modules. (hybrid modules include icons.).

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

Worldwide Headquarters
North America
 Watertown, CT USA
 Phone (1) 860 945 4200 US
 Phone (1) 888 425 6165

Regional Headquarters
Europe/Russia/Africa
 Chertsy, Surrey, England
 Phone (44) 0 1932 571771

Regional Headquarters
China
 Shanghai, P.R. China
 Phone (86) 215385 0303

Regional Headquarters
Latin America
 Bogota, Colombia
 Phone (571) 657 1950/51/52

Regional Headquarters
Middle East
 Dubai, United Arab Emirates
 Phone (971) 4 3689743
 Phone (971) 50 5518716

Regional Headquarters
Asia/Pacific
 Frenchs Forest
 Sydney, Australia
 Phone (86) 21 5385 0303

Siemon Interconnect
Solutions
 Watertown, CT USA
 Phone (1) 860 945 4213 US
 www.siemon.com/SIS