

S110[®] 4-Pair Termination Tool

Seats 3-, 4-, and 5-pair 110 blocks

- Replaceable head and cutting blades
- Terminates wires on both the cable and the cross-connect side of 110 blocks
- Compact design can be used with disconnect or modular jack panel 110 blocks
- Compatible with 4-pair work area products
- Ergonomically designed handle




1 To remove the head of the tool for blade replacement, twist and pull the head from the tool body.




2 Slide the trimming blades and wire seating assembly out of tool head.

Caution: Blades are extremely sharp. Exercise caution when handling.



3 Remove the cutting blades from the assembly. Rotate 180° and place back into position.



4 Slide the combined trimming blade/seating assembly back into position inside the tool head. Examine the assembly to ensure proper alignment of all components.



5 Snap the head onto the shaft of the tool and rotate it until it locks into position.



6 Terminate and trim the conductors into the 110 wiring base using the cutting edge of the tool.



7 Insert a 110C connecting block into the head of the tool, carefully align over the wiring base and punch down on the block.



8 Lace cross-connect cable into the 110C block and terminate.

Ordering Information

Ordering Information

S788J4HReplacement head
S788J4B.....Cutting blades

To assist safe installations, comply with the following:

- A. Use caution when installing or modifying telecommunications circuits.
- B. Never touch uninsulated wire terminals unless the circuit has been disconnected.
- C. Never install this device in a wet location.
- D. Never install wiring during a lightning storm.



**Worldwide Headquarters
North America**
Watertown, CT USA
Phone (1) 860 945 4200 US
Phone (1) 888 425 6165

**Regional Headquarters
EMEA**
Europe/Middle East/Africa
Surrey, England
Phone (44) 0 1932 571771

**Regional Headquarters
Asia/Pacific**
Shanghai, P.R. China
Phone (86) 21 5385 0303

**Regional Headquarters
Latin America**
Bogota, Colombia
Phone (571) 657 1950

