



# CATEGORY 8.2 E20 LSFR0H S/FTP CABLE (International)

Siemon's Category 8.2 cable exceeds the transmission performance requirements of IEC 61156-9 up to 2000 MHz. This fully shielded cable supports 30-meter Class II as well as 100-meter class F<sub>A</sub> balanced cabling performance (ISO/IEC 11801-1 draft) to meet IEEE 802.3bq 25 Gb/s (25GBASE-T) and 40 Gb/s (40GBASE-T) applications in the data center. As part of a Class II twisted-pair cabling system which shares open and common specifications, interoperability and backwards compatibility are ensured with the reach to support a broad range of architectures for switch-to-server connections, including switches placed in top of rack (ToR), middle of row (MoR) and end of row (EoR). With an LSFR0H cable jacket qualified for mechanical reliability in high temperature environments up to 75°C, Siemon's S/FTP Category 8.2 cable features individual foils around each pair and a high screen coverage outer braid to provide superior noise immunity and coupling attenuation performance.



## COMPLIANCE

- ISO/IEC 11801-1 (Class II) draft
- EN 50173-5
- IEC 61156-9
- LSFR0H: IEC 60332-3-24, IEC 60754, and IEC 61034

## CABLE CONSTRUCTION

- S/FTP
- Reverse sequential measurement markings on jacket
- Pairs individually shielded with aluminium bonded polyester tape
- Overall tinned-copper wire braid

## APPLICATIONS SUPPORT

- 40GBASE-T
- 25GBASE-T
- 10GBASE-T
- 1000BASE-T
- 100BASE-T
- 10BASE-T
- IEEE 802.3 af (PoE)
- IEEE 802.3 at (PoE<sup>+</sup>)

# PRODUCT INFORMATION

## ELECTRICAL SPECIFICATIONS

DC Resistance	< 2.1 Ω/30m
DC Resistance Unbalance	within pairs ≤ 2%
	between pairs ≤ 5%
Mutual Capacitance	1.29 pF/30m
Characteristic Impedance (ohms)	100 MHz: 100 ± 5%
NVP	76%
TCL	≥ 50-15 x log (f)dB
Delay Skew	≤ 7.5ns/30m

## PHYSICAL PROPERTIES

	LSFROH
Pulling Tension (max)	110N (25 lbf)
Bend Radius (min)	32mm (1.3 in.)
Installation Temperature	0 to 75°C (32 to 167°F)
Storage Temperature	-20 to 75°C (-4 to 167°F)
Operating Temperature	-20 to 75°C (-4 to 167°F)

## TRANSMISSION PERFORMANCE

GUARANTEED WORST CASE
  SIEMON TYPICAL

Frequency (MHz)	Insertion Loss (dB/30m)		NEXT (dB)		PS NEXT (dB)		ACR (dB)		PSACR (dB)		ACR-F (dB)		PS ACR-F (dB)		Return Loss (dB)		Propagation Delay (ns)	
	Guaranteed Worst Case	Siemon Typical	Guaranteed Worst Case	Siemon Typical	Guaranteed Worst Case	Siemon Typical	Guaranteed Worst Case	Siemon Typical	Guaranteed Worst Case	Siemon Typical	Guaranteed Worst Case	Siemon Typical	Guaranteed Worst Case	Siemon Typical	Guaranteed Worst Case	Siemon Typical	Guaranteed Worst Case	Siemon Typical
1	1.1	0.7	78.0	80.9	75.0	88.0	76.9	80.2	73.9	87.4	78.0	85.6	75.0	84.1	20.0	21.6	171.0	144.0
4	1.1	1.1	78.0	91.3	75.0	96.2	76.9	90.2	73.9	95.1	78.0	92.7	75.0	90.7	23.1	31.8	165.4	140.0
10	1.8	1.6	78.0	99.6	75.0	96.2	76.2	98.0	73.2	94.6	78.0	97.3	75.0	95.5	25.0	35.9	163.4	138.0
16	2.2	2.1	78.0	101.0	75.0	89.6	75.8	98.9	72.8	87.5	76.5	101.0	73.5	95.8	25.0	29.8	162.8	137.0
20	2.5	2.3	78.0	98.1	75.0	96.5	75.5	95.8	72.5	94.2	74.7	95.9	71.6	94.2	25.0	30.6	162.5	137.0
31.25	3.2	3.0	78.0	98.2	75.0	97.9	74.8	95.2	71.8	94.9	70.7	95.2	67.7	92.5	25.0	30.2	162.0	136.0
62.5	4.5	4.2	78.0	101.0	75.0	92.2	73.5	96.8	70.5	88.0	64.7	93.9	61.7	89.8	23.6	32.5	161.4	136.0
100	5.5	5.1	75.4	100.0	72.4	94.7	69.9	94.9	66.9	89.6	60.6	92.7	57.6	89.4	22.2	34.6	161.1	136.0
200	7.9	7.3	70.9	101.0	67.9	89.5	63.0	93.7	60.0	82.2	54.6	91.0	51.6	85.2	20.1	30.8	160.8	135.0
250	8.9	8.2	69.4	99.1	66.4	88.2	60.5	90.9	57.5	80.0	52.6	88.3	49.6	85.6	19.4	26.6	160.7	135.0
300	9.8	9.0	68.2	99.3	65.2	88.7	58.4	90.3	55.4	79.7	51.1	86.0	48.1	84.3	18.8	20.4	160.6	135.0
350	10.6	9.8	67.2	97.2	64.2	86.1	56.6	87.4	53.6	76.3	49.7	84.1	46.7	81.6	18.4	29.4	160.6	135.0
400	11.4	10.4	66.4	101.0	63.4	88.3	55.0	90.6	52.0	77.9	48.6	85.2	45.6	80.8	18.0	26.6	160.6	135.0
550	13.5	12.3	64.3	97.3	61.3	85.5	50.8	85.0	47.8	73.2	45.8	80.9	42.8	80.4	17.0	29.5	160.5	135.0
600	14.1	12.9	63.7	99.5	60.7	84.8	49.6	86.6	46.6	71.9	45.0	80.0	42.0	80.0	16.8	23.1	160.5	135.0
800	16.5	14.9	61.8	93.9	58.9	81.0	45.3	79.0	42.4	66.1	42.5	78.2	39.5	74.1	15.9	26.0	160.4	135.0
900	17.6	17.6	61.1	97.3	58.1	78.7	43.5	79.7	40.5	61.1	41.5	77.4	38.5	73.6	15.5	28.5	160.4	135.0
1000	18.6	16.7	60.4	96.1	57.4	79.9	41.8	79.4	38.8	63.2	40.6	76.5	37.6	72.7	15.2	32.7	160.3	135.0
1600	24.0	21.6	57.3	97.5	54.3	74.1	33.3	75.9	30.3	52.5	36.5	69.7	33.5	67.6	13.8	19.5	160.3	135.0
2000	27.2	24.6	55.9	87.9	52.9	64.9	28.7	63.3	25.7	40.3	34.6	64.2	31.6	63.3	13.1	19.4	160.3	135.0

All performance based on 30 meters

## Ordering Information:

Part #	Description
9T82H4-E2008R1N.....	LSFROH (IEC 60332-3-24), Violet Jacket, 305m
9T82H4-E2008R2N.....	LSFROH (IEC 60332-3-24), Violet Jacket, 500m

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

**Worldwide Headquarters**  
**North America**  
 Watertown, CT USA  
 Phone (1) 860 945 4200

**Regional Headquarters**  
**Europe Africa**  
 Chertsey, Surrey, England  
 Phone (44) 0 1932 571771

**Regional Headquarters**  
**China**  
 Shanghai, P.R. China  
 Phone (86) 215385 0303

**Regional Headquarters**  
**Latin America**  
 Bogota, Colombia  
 Phone (571) 657 1950/51/52

**Regional Headquarters**  
**India Middle East**  
 Dubai, United Arab Emirates  
 Phone (971) 4 3689743

**Regional Headquarters**  
**Asia Pacific**  
 Sydney, Australia  
 Phone (86) 21 5385 0303

**Siemon Interconnect Solutions**  
**Watertown, CT USA**  
 Phone (1) 860 945 4213 US  
 www.siemon.com/SIS