

V600 42U Shock Pallet and Ramp

Siemon Interconnect Solutions (SIS) offers an environmentally friendly packaging method to ship our V600 cabinets. When requested, the V600 cabinet ships on a shock pallet designed to ensure the cabinet is capable of handling the additional weight of loaded network equipment and that the cabinet and installed components are protected during transport. Our pallet coupled with the re-usable corrugate packaging system provides a cost-effective, sustainable solution for rapid cabinet deployment.

Cabinet Load – Cabinet supports load of 3000 lbs (static). 2,250 lbs (dynamic).

ISTA Design – Pallet and cabinet support system are designed to comply with International Safe Transit Association (ISTA) Part 3E to provide a simulation of the general damage producing motions, forces, conditions and sequences of transport environments.

Top of Pallet and Ramp – reinforced with steel channels to guide casters and ensure smooth roll off.

Polyethylene Foam Support – The foam structure within the pallet design provides a resilient, high efficiency packaging and cushioning material. Its superior properties absorb repetitive shocks during transportation protecting valuable electronic products.

Certified Timber Materials – Pallet materials are heat treated and produced in compliance with International Plant Protection Committees ISPM 15: Guidelines for Regulated Wood Packaging Material in International Trade.



Rapid Cabinet Deployment - The cabinets can be conveniently configured, tested and packaged at any location and then shipped to your customer for quick and safe deployment. A tip sensor is attached to the packaging to show if the product has tipped during transport.

Cabinet Ordering Information

Part #	Description
V6(X)A-(X)(X)(X)(X)1-42P	V600 Cabinet, 42U, Black, with Shock Pallet*
Cabinet Depth	Caster Option
1 = 1000mm (40 in.)	2 = Casters
2 = 1200mm (48 in.)	
Side Panels	Lock Type
0 = No Side Panels	1 = Key Lock
1 = 1 Side Panel	2 = Tumbler Lock
2 = Side Panels	
Front Door	Rear Door
A = Full Vented	A = Full Vented
B = Split Vented	B = Split Vented
C = Split Solid	C = Split Solid



Includes 4 leveling feet, 50 cage nuts, 4 casters and 2 stabilizing brackets

* Ramp sold separately. See ordering information below.

Note: Proper handling of packaged, loaded cabinet is very important. It is recommended to use a shipping company who has experience in specialized handling of packaged network equipment. Please contact Siemon Company SIS customer service if you would like further information.

Ramp

The 6 degree ramp allows for a loaded cabinet on casters to be safely deployed. The top surface is reinforced by two steel channels which help guide the casters. Two velcro straps are used to securely and quickly attach the ramp to the pallet to assist with quick deployment. - Able to use 5 times.

Note: Ramp usage of 5 times based on maximum loaded cabinet



Part #	Description
V6-RAMP	Ramp for use with V600 Cabinet and Shock Pallet 1295mm (51 in.) x 965mm (38 in.) x 203mm (8 in.) Weight: (68 lbs.)

SIS_SS_ShockPallet_B 1/16

© 2016 Siemon

**Worldwide Headquarters
North America**
Watertown, CT USA
Phone (1) 860 945 4200 US
Phone (1) 888 425 6165

**Regional Headquarters
EMEA**
Europe/Middle East/Africa
Surrey, England
Phone (44) 0 1932 571771

**Regional Headquarters
Asia/Pacific**
Shanghai, P.R. China
Phone (86) 21 5385 0303

**Regional Headquarters
Latin America**
Bogota, Colombia
Phone (571) 657 1950

**Siemon Interconnect
Solutions**
Watertown, CT USA
Phone (1) 860 945 4213 US
www.siemon.com/SIS